

Sonex Classic Wall Panels

Sonex Classic Panels feature a modified anechoic wedge design for cost-effective, yet impressive sound control. The unique geometric shape of the surface pattern on these panels provides optimum absorption, making them an excellent choice for recording and broadcast studios.



Sonex Classic Panels can also be used in listening rooms, restaurants, production areas and other locations where sound absorption is critically important.

Panels offer excellent acoustical control across all frequencies with Noise Reduction Coefficients (NRC) ranging from 0.75 to 0.80.

Made of a Class 1 fire-rated melamine foam, Sonex Classic panels are available in natural, painted, or Colortec finishes.

Coefficients per ASTM C423-90a

	125Hz	250Hz	500Hz	1kHz	2kHz	4kHz	NRC
2" Natural	0.05	0.31	0.81	1.01	0.99	0.95	0.80
2" Painted	0.17	0.33	0.85	1.03	1.08	1.06	0.80
2" Hypalon	0.05	0.31	0.81	0.96	0.97	0.97	0.75

Panel Size	Standard 24" x 48"; Custom sizes available
Panel Thickness	2"
Fire Resistance	ASTM E 84 Class 1
Finish	Natural white or Natural gray; Hypalon options available
Installation	Sonex Acoustic latex adhesive; adheres to wall paneling, wood, plywood, metal and concrete

West General LLC
 1475 Saratoga Ave, Suite 120
 San Jose, CA 95129
 Phone: 408-255-8644 Fax: 408-255-8677
www.westgeneral.com